

# RTP10 *10,000 lbs. capacity* *Two Post Lift*



Shown:  
RTP10N000  
10,000 lbs.  
(4535kg)  
capacity

## FEATURES:

- 3-stage front arms enable greater pickup point access
- Top mounted pull design cylinder protects piston inside of carriage
- Two full-stroke cylinders with overhead cable for equalization
- Spring operated arm restraints, disengage at floor level
- Padded overhead switch bar
- Single point lock release
- Large rubber-padded swivel adapters with extra height extensions are standard

Specifications	RTP10
Capacity	10,000 lbs. (4535kg)
Rise	76-1/8" (1934mm)
Overall Height	143" (3632mm)
Overall Width	131" (optional 137") (3327-4380mm)
Drive Through Clearance	99" (optional 105") (2515-2667mm)
Overhead Switch Height	137-5/8" (3496mm)
Front Reach (Min/Max)	23"/44-1/2" (584mm/1130mm)
Rear Reach (Min/Max)	38-1/2" / 58" (978mm/1473mm)
Min/Max Adapter Height	3-5/8" / 8-5/8" (792mm/219mm)
Width Inside Column	109" (optional 115") (2769mm/2921mm)
Voltage/Amps	208/230, 20 amps
Motor/Phase	1ph*/2HP/50Hz 1ph*/2HP/60Hz
Ceiling Height Required	144" (3658mm)

\*Optional 3-phase available.



2212 Camplain Road  
Hillsborough, NJ 08844  
1-888-8FC-LIFT