

RTP12 *12,000 lbs. capacity* *Two Post Lift*

Specifications	RTP12
Capacity	12,000 lbs. (5443kg)
Rise (with adapters)	82-1/2" (2096mm)
Adjustable Overall Height	165-1/4" (4197mm) 177" high setup (4496mm)
Overall Width	150-3/8" (3820mm)
Drive Through Clearance	109-1/2" (2781mm)
Overhead Switch Height	159-3/8" low/171-3/8" high (4048mm / 4353mm)
Front Reach (Min/Max)	38-1/2" min/57-1/2" max (878mm / 1460mm)
Rear Reach (Min/Max)	38-1/2" min/57-1/2" max (878mm / 1460mm)
Lifting Pad Height	6" (152mm) 10-1/2" w/short extension (267mm) 14-1/2" w/high extension (368mm)
Width Between Columns	123-1/4" (3130mm)
Voltage/Amps	208/230, 20 amps
Motor/Phase	1ph*/2HP/50Hz 1ph*/2HP/60Hz
Speed of Rise	60 seconds

*Optional 3-phase available.



FEATURES:

- Single point lock release
- Overhead cable equalization.
- Top mounted pull design cylinder protects piston inside of carriage
- Padded overhead height limit switch bar.
- Spring operated arm restraints, disengage at floor level.
- Large rubber-padded swivel adapters with 4.5" and 8.5" (114mm - 216mm) extra height extensions.



2212 Camplain Road
Hillsborough, NJ 08844
1-888-8FC-LIFT