

Two - Post Lift / 12,000 lbs. capacity

FEATURES:

- 2-stage front and rear arms
- Two full-stroke cylinders with overhead cable for equalization
- Spring operated arm restraints, disengage at floor level
- Adjustable overhead heights available*
- Adjustable width and drive-thru settings
- Padded overhead switch bar
- Single point lock release
- Large frame-engaging swivel adapters with extra height extensions are standard
- Durable powder coat finish

Low-Profile Adapter Design

The R12 features low-profile, oversized pads with extensions to raise most vehicles on the road today. Includes four (each) adapter extensions at 3.5" and 5" (89mm, 127mm) - includes column storage





Specifications	R12
Capacity	12,000 lbs. (5443kg)
Maximum Rise	77-1/2" (1968mm) With 5" adapter extension
Adjustable Overall Height Options	166" (4216mm) Standard Height 178" (4521mm) Extended Max. Height* 154" (3912mm) LH1 143" (3632mm) DP
Overall Width	140" or optional 146" (3556 / 3708mm)
Drive Through Clearance	102-3/4" or optional 108-3/4" (2609 / 2762mm)
Overhead Switch Height Options	160-1/8" (4067mm) Standard 172-1/8" (4524mm) Extended* 148-1/8" (3762mm) LH1 137-1/8" (3483mm) DP
Front Reach (Min./Max.)	35"/ 54" (889 / 1372mm)
Rear Reach (Min./Max.)	35"/ 54" (889 / 1372mm)
Min./Max. Adapter Height	4-3/4" (120) w/ no adapter extension 9-3/4" (248mm) w/ 5" adapter extension
Width Inside Column	120-7/8" (3070mm) Standard 114-7/8" (2918) Optional
Voltage/Amps	208/230, 12 amps; 208/230, 16 amps
Motor/Phase**	1ph**/2HP/50Hz; 1ph**/2HP/60Hz
Ceiling Height Required	168" (4267mm)

^{*}Hose and cable kit required **Optional 3-phase available



Revolution's R12 is ALI Certified. The R12 lift meets the highest industry safety and performance standards. Look for the Gold label.







■ phone: 812.273.1622 ■ sales@revolutionlift.com

