

ENGINEERED TO PERFORM. BUILT TO LAST.

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.

Low-profile design with 4" drive-over height for effortless positioning of vehicles.

DOUBLE SCISSOR LIFT 7,700 lbs. Capacity

FEATURES:

Exclusive Inverse Piston Synchronization equalization system ensures worry-free use

- · Low drive-over height allows for easy vehicle positioning
- 78-5/8" rise height
- 24-3/4" wide platforms accommodate a range of vehicles and pickup points
- · Durable, diamond plate finish
- Patent pending equalization system with 26 lock positions
- Surface or flush mounted option



Hinged ramps with polymer rollers drop down to a 65 degree angle for easy access for wheel and brake service.

The ramps fold up, lock in place and increase lifting capabilities by extending the pick-up point surface area.









Polymer rubber adapter pads are used for vehicle contact.

Durable diamond plate platform to maintain rubber block positioning




996 Industrial Drive Madison, IN 47250





www.forwardlift.com

Phone: 800.423.1722 Fax: 812.273.7329



Ramp Length

Forward Lifts meet the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



SPECIFICATIONS FS77N0000MBL/RD*

Capacity 7,700 lbs. (3500kg)

FS77N0000MBL

78-5/8" (2000mm surface mounted Maximum Rise 74-1/2" (1895mm) recessed mounted

Lowered Height 4-1/8" (105mm) Overall Width 85" (2159mm)

Overall Length 85" (2159mm) Platform width 24-3/4" (629mm)

Width Between Platforms 23-5/8" (600mm) 59" (1499mm)

Platform Length 85" (2159mm) w/ramps extended 13" (330mm)

Max. Distance from Console to Lift 85" (2159mm) Voltage 230V

Motor/Phase 1ph/4HP/60Hz Rise Time 39 seconds

Compressed Air Connection 85-110psi