

DIRECTION



CLFP9

SITE SPECIFICATIONS

BAY HEIGHT: 10' 2" minimum

• BAY WIDTH: 12' recommended

BAY DEPTH: 24' recommended

- POWER REQ.: 208-230v Single Phase*, 30-amp breaker
- MIN. CONCRETE SPEC: 4" thick, reinforced, free from cracks/seams, rated at 3500+ psi, cured at least 28 days

Model Number	CLFP9
Lifting Capacity	9,000 lbs.
Lifting Configuration	Symmetric
Arms	3-stage front/3-stage rear
Overall Height	120.875″
Rise Height	78.125″
Screw Pad Height	4" / 5.875"
Overall Width	137.5"
Inside Columns	109″
Drive-Thru Clearance	98.187"
Floor to Overhead Switch	-
Front Arm Reach	24.5" / 44.5"
Rear Arm Reach	24.5" / 44.5"
Motor / Voltage	2HP, 208v-230v, 60Hz, 1Ph
Speed of Rise	50 s
Ceiling Height Required	10′ 2″
ALI/ETL Certified	-
2' Height Extension Available	-
3' Height Extension Available	-
Colors Available	

^{*3-}phase upgrade is available for purchase

www.challengerlifts.com 1-800-648-5438